

USB TV BOX

Order NO. 1680010

Format :

Support NTSC / PAL / SECAM color system

Video

Capture up to 30 fps at CIF format (352 x 288 pixels). It provides a high quality motion video to suit your action

Support hardware & software snapshot function. You can choose to snapshot pictures by software, or just a simple click on the hardware

scalable video window size from 80 x 60 up to 640 x 480 pixels. The user-friendly application program offers you the flexibility of multi-windows

Support TWAIN interface for image editing applications

Audio

32KHz/ 44.1KHz sampling-rate (Optional)

TV Tuner :

Module	Philips or equivalent
TV system	NTSC PAL BG, I, DK SECAM BG, DK, LL
BTSC(MTS)	(Optional)
NiCAM	(Optional)
Teletext	(Optional)



Interface :

Bus	Hot Plug & Play (No need to turn off your PC when installing) External USB V1.0
Input	One RF (TV Tuner) input One yellow RCA-Jack (CVBS) input One mini-din(S-Video/Y-C) input One FM (Radio) input, (Optional) One DC Power input
Output	One stereo audio (Line-out) output One internal speaker(8 ohms, 0.5W) (Optional) One white RCA-Jack(CVBS) output (Optional)

Remote-Control

(Optional)

Power

Low power consumption

Ideal for portable computer

System requirement

PentiumII or Higher PC with USB interface

64MB up to system memory

Microsoft Windows 98 or higher version

Microsoft DirectX6 or higher version

Minimum 8MB free hard disk drive space

Remarks

Support iMAC will be available

YOKOJIMA PERIPHERAL INDUSTRIAL CO., LTD.

6F. NO.15 ,LN.131,HANG CHOW SOUTH ROAD,SEC 1 TAIPEI

TAIWAN,R.O.C

TEL886-2-2321-4118 FAX:886-2-2391-0073

E-mail:yokojima@ms8.hinet.net